

POWER DISTRIBUTION UNITS (PDUs)



“Estep offers a wide PDU product range”

- Basic PDU's
- Metered PDU's
- Monitored and managed PDU's
- On demand manufacturing
- Compliant with relevant standards
- With/without on/off switch
- Suitable for mounting inside the cabinet
- Easy to mount and maintain

PDU



Basic PDU

Part number *	Product definition	W x D x H (mm)
M443AL-ES	3xDIN49440 Socket Schuko PDU, 19" 1U, aluminium profile frame, 1x16A MCB, 4000 Watt, 250V AC, 3x1.5mm ² , 3m cord with DIN 49441 plug, CE mark	W= 482,6 (19") D= 44,4 H= 44,4
M446AL-ES	6xDIN49440 Socket Schuko PDU, 19" 1U, aluminium profile frame, 1x16A MCB, 4000 Watt, 250V AC, 3x1.5mm ² , 3m cord with DIN 49441 plug, CE mark	W= 482,6 (19") D= 44,4 H= 44,4
M446STD-ES	6xDIN49440 Socket Schuko PDU, 19" 1U, aluminium profile frame, 16A On/Off Lighted Switch, 4000 Watt, 250V AC, 3x1.5mm ² , 3m cord with DIN 49441 plug, CE mark	W= 482,6 (19") D= 44,4 H= 44,4
M449ALC-ES	9xDIN49440 Socket Schuko PDU, 19" 2U, aluminium profile frame, 1x16A MCB, 4000 Watt, 250V AC, 3x1.5mm ² , 3m cord with DIN 49441 plug, CE mark	W= 482,6 (19") D= 44,4 H= 88,8
M446AL UK-ES	6xBS1363 UK Socket PDU, 19" 1U, aluminium profile frame, 16A On/Off Lighted Switch, 4000 Watt, 250V AC, 3x1.5mm ² , 3m cord with 13A BS1363 plug, CE mark	W= 482,6 (19") D= 44,4 H= 44,4
M441842ALD-ES	18xDIN49440 Socket Schuko PDU – double circuit (9+9) ZeroU, aluminium profile frame, 2x16A MCB, 250vac, suitable for 42U rack mounting, without cord	W= 1890 D= 42 H= 60
M446ALD-ES	6xDIN49440 Socket Schuko PDU, -double circuit (3+3) 19" with aluminium profile frame, 2x16A MCB, 4000 Watt, 250V AC, 3x1.5mm ² , 2,5m cord with DIN 49441	W= 482,6 (19") D= 42 H= 60
M44 6AL IEC-ES	6xIEC 320 C13 Socket PDU, 19" aluminium profile frame, 1x16A MCB, 4000 Watt, 250V AC, IEC 320 C14 plug	W= 482,6 (19") D= 42 H= 60

Metered PDU

Part number	Product definition	W x D x H (mm)
M446AL IEC AMP	6xIEC 320 C13 Socket PDU with Ampermeter Display, 19" 1U, aluminium profile frame, 1x16A MCB, 4000 Watt, 250V AC, 3x2.5mm ² , 3m cord with IEC60309 plug (16A 2P+E), CE mark	W= 482,6 (19") D= 44,4 H= 44,4
M44 24AL IEC AMP MCB	24xIEC 320 (20xC13 + 4xC19) Socket PDU with Ampermeter Display, ZeroU, aluminium profile frame, 2x16A MCB, 8000 Watt, 250V AC, 3x6.0mm ² , 3m cord with IEC60309 plug (32A 2P+E), CE mark	W= 1648 D= 44,4 H= 62

Monitored & Managed IP PDU

Part number	Product definition	W x D x H (mm)
M44 20AL IEC MONITOR	20xIEC 320 (16xC13 + 4xC19) Socket MONITORED IP PDU with Ampermeter Display, ZeroU, aluminium profile frame, 2x16A MCB, 8000 Watt, 250V AC, 3x6.0mm ² , 3m cord with IEC60309 plug (32A 2P+E) ,CE mark, daisy-chain function upto 10 units, Remote Monitoring port	W= 1744 D= 88,8 H= 44,4
M44 20AL IEC MANAGED	20xIEC 320 (16xC13 + 4xC19) Socket, Socket Based MANAGED IP PDU with Ampermeter Display, ZeroU, aluminium profile frame, 2x16A MCB, 8000 Watt, 250V AC, 3x6.0mm ² , 3m cord with IEC60309 plug (32A 2P+E) ,CE mark, daisy-chain function upto 10 units, Remote Monitoring port	W= 1744 D= 88,8 H= 44,4



* Fixing pieces is included to the PDU box.