


Product information

FO Field SC, Grade Cf, APC, green, G657.A fiber stub, 250µm fibers up to 0.9mm fibers

R820792
1 pcs



Field-terminable SC / APC connector, Grade Cf/1, individual packaged incl. stripping chart and QR code with installation instructions. Color green, strain relief pigtail white.

090.7337

Technical Data


DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	UL Listed according to IEC 61754-4
Protection class IP	IP 20
Connector class	connector
Connector type (A)	SC
Polishing plug (A)	APC 8°
Attenuation grade IL (A)	C
Connector color (A)	green

Climatic Data


DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Operation temperature	10 °C to 60 °C / +50 °F to +140 °F

Field-terminable connector, SC APC, Grade Cf/1, in compliance with IEC 61754-4 (SC) and FprEN 50377-17-1 (draft of standard for field-terminable connectors).

Connector housing made of PBT/UL-94 V-0, green, (singlemode APC), fiber stub with 8° cleaved fiber, red semi-transparent push button for fiber fixation and function testing.

	Description	PU	Product No.
	FO-Cleaning tool kit	1 pcs	R319903

	Description	PU	Product No.
	Cletop Cleaning Spare Cassette	1 pcs	R319904
	Red Light Source, 2.5+1.25 mm ferrules	1 pcs	R504313
	Lose tube ø0.5/0.9mm, 5m, transparent	1 pcs	R821300
	Ferrule Mate, 2.50 mm, for E-2000™ /FC/SC/ST	1 pcs	R319902
	FO Field Divider	1 pcs	R823877
	FO Field Patch set 2.0mm	10 pcs	R841480
	FO Field Patch set 3.0mm	10 pcs	R841479

	Description	PU	Product No.
	Boot 90° R30	12 pcs	R505756