

Product information

Installation Cable Cat. 6A, U/UTP, 4P, 650 MHz, LSZH, Eca, Ø 7.7mm, WARP, 500 m

R814611
500 m



Solid wire installation cable U/UTP Cat. 6_A. 100 Ohm impedance. Data transmission frequencies of up to 650 MHz.

090.7840 / similar product

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO/IEC 11801-1 Ed 1.0 2017-11 EN 50173-1 TIA 568-C.2 IEC 61156-5 IEC 60332-1-2 UL 1666 CPR fire class: EN50575 IEC 60754-2
Protection class IP	IP 20
PoE	Yes
Cable type	installation cable
Category	Cat. 6 _A ISO
Shielding	U/UTP
Jacket material	LSZH
Fire rating	Eca
Cable jacket characteristics	Flame-retardant
Cable protection	No protection
Cable overall diameter	Ø 7.7 mm
Conductor	AWG 23
Cable design	normal
Number of wires	8
Stranding	4 pairs
Wire type	Wire
Max. test frequency	650 MHz

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	500 m
Color	gray