


Product information

Central Loose Tube Cable I/A-DQ(ZN=B)H, G.652.D, Eca, 6-fibers

R304145
2000 m



030.1402.1 / similar product

This cable construction features a central gel-filled loose tube with a diameter of 2.8 mm for 2 - 16 fibers or 3.5 mm for 18 - 24 fibers. The reinforced glass yarns enhance strength and tensile force and is making it to your ideal partner for secondary cabling applications (backbone) in generic cabling systems.

- Sheath: LSZH, green
- Fiber: singlemode (SM) E9/125

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	IEC 60794-1-2 E11 IEC 60794-1-2 E3 IEC 60794-1-2 F1 IEC 60332-1 IEC 60332-3C IEC 61034 IEC 60754-2 ISO/IEC 11801:2002 ITU-T G.652.D IEC 60793-2-50:2004, B 1.3 IEC 60794-1-2 E1
Cable type	loose tube
Jacket material	LSZH
Fire rating	Eca
Cable jacket characteristics	Cable, water-tight Cable, metal-free Zero-halogen
Cable protection	Rodent protection
Cable overall diameter	6.5 mm
Cable design	U-DQ(ZN)BH
Fiber type	singlemode (SM)
Fiber class	G.652.D (OS1, OS2)
Number of fibers	6
Conductor type	loose tube, gel-filled
Fiber diameter	E9 / 125 µm

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	2000 m

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Color	green